



## Main

Range	SpaceLogic
Product name	SpaceLogic TC900
Device short name	TC903
Product or component type	Thermostat
Sensor type	100 kOhm NTC thermistor

## Complementary

Device application	Fan
Product specific application	2-pipe system
[Us] rated supply voltage	24 V AC 50/60 Hz
Network frequency	50 Hz 60 Hz
Max power consumption in W	1 W
Communication port protocol	-
Function available	Setpoint adjustment Fan control Mode selection Economiser Disable functions Alarm Low temperature protection
Colour	White
Housing colour	White
Control type	mechanical, for thermostat pulse width modulation, for actuator 3 speed control relay, for fan
Display type	Backlit LCD screen
Information displayed	Ambient room temperature 0 to 50 °C Time Day

	Temperature alarm Communication status ok Current program
Measurement accuracy	Temperature: +/- 1 °C,
Output voltage	240 V AC 5 A for relay 240 V AC 2 A for load
Connections - terminals	Screw terminal (back) - 2 cable(s) Screw terminal (back) - 1 cable(s)
Width	86 mm
Depth	40 mm
Height	86 mm
Market segment	Small buildings Hotel Healthcare Residential

## Environment

Temperature setting range	5...35 °C
Relative humidity	5...95 %
Ambient air temperature for operation	0...50 °C
Standards	EN/IEC 60730-1 EN/IEC 60730-2-9
Product certifications	CE
IP degree of protection	IP20
Pollution degree	2

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>